



Type PBH  
Key Selector Switches

- $\Phi$  22mm
- Front bezel ( Aluminium);standard,circular
- Holder : Metal,Plastic, Nut
- Self-hold or spring return
- Two and three positions
- IEC/EN 60947-5-1,UL 508,IEC/EN 60073, IEC/EN 60529

Dimensions and style

- 22A =  $\Phi$ 22mm Metal holder
- 22B =  $\Phi$ 22mm Plastic holder
- 22D =  $\Phi$ 22mm Nut holder

Actions

- 21=Two positions L R
- 31=Three positions L C R

Key extraction position※

- L = on the left position
- C = on the center position
- R = on the right position

Product description

Key selector switches are mechanical switches that can be turned right, center or left to open or to close the electric contacts. Mostly used to switch between two/three circuits. when the key is pulled -out no any other action can be done. They should be ordered in parts(operator +holder+contact block) and installed in an enclosure.

Type

Y= Key Selector Switches

General data

Peripheral of actuator	AL
Actuator	PA
Mechanical life	$\geq 3 \times 10^6$ Cycles
Operating temperature	-25 to + 70°C ( -13 to +158°F )
Storage temperature	-30 to + 80°C ( -22 to +176°F )
Protection Degree	IP 65

Order code

Type	Actions	Dimension & holder	Contact	Part No.
Key Selector Switches	2-Positions	$\Phi$ 22mm Metal holder	In place of □ insert contact as follows:	PBH-22A-□Y▲■
		$\Phi$ 22mm Plastic holder	2NO : 20	PBH-22B-□Y▲■
		$\Phi$ 22mm Nut holder	2NC : 02	PBH-22D-□Y▲■
	3-Positions	$\Phi$ 22mm Metal holder	1NO : 10	PBH-22A-□Y▲■
		$\Phi$ 22mm Plastic holder	1NC : 01	PBH-22A-□Y▲■
		$\Phi$ 22mm Nut holder	1NO+1NC : 11	PBH-22A-□Y▲■
			For contact details, See pg.32	PBH-22B-□Y▲■
				PBH-22D-□Y▲■

1. In place of ▲ insert actions table
2. In place of ■ insert Key extraction position table

Dimensions (mm)

