

## Ø22mm Indicator compact High-intensity illuminated



- Compact, high-intensity illuminated, reliable LED indicator for safe status indication, for use in many types of applications including machinery, Industrial automation, robotics and special vehicles.
- Compact design with a rear panel thickness of only 9.5 mm to meet the requirements of miniaturization of large sets
- Straight-in fast connection model, PIT wire 0.75mm<sup>2</sup>
- A variety of colors, red, green, yellow, orange, blue, ice blue, purple and white, are available
- IP67

### □ Specifications

CE

Code	LS22-D
Mounting size	Ø22mm
Working Voltage	24VAC, 12~30VDC
Working Current	<30mA
Function	Steady
Material	Lens-PC, Based-PA, Nut-PA
Operating environment	Working Temperature: -20°C ~ +55°C (No Freezing) Store Temperature: -30°C ~ +80°C (No Freezing) Humidity: 40 ~ 85%RH (No Condensation)
Vibration resistance	10 ~ 55Hz, Amplitude 0.75mm
Color	Lens: transparent LED: Red, Green, Yellow, Blue, Amber, Ice Blue, Violet, White
Connector type	Push-in terminal (PIT), wire 0.2~1.5mm <sup>2</sup>
Useful life (reference)	50000 hrs (when 25 °C, brightness is 50% below initial value)
Protection class	IP67

### □ Outline Dimensional drawing (mm)

