

Type PB Emergency Stop Switch Illuminated Emergency Stop Switch

- $\Phi 22\text{mm}$
- Push-to-lock, Pull or Turn-to-reset operator
- Direct opening action mechanism
- Illuminated switches are available
- Arrow marked and unmarked buttons
- Two models of contact
- IEC/EN 60947-5-1, UL 508, IEC/EN 60073, IEC/EN 60529



Product description

The STOP function is obtained by pushing the head while the pushing the head while the reset is obtained by turning clockwise the head or the key. It is used in dangerous situations When emergency measures are required.

Type

Z = $\Phi 40\text{mm}$ Mushroom Red
ZD = $\Phi 40\text{mm}$ Mushroom Red illumination

Actions

Blank = Push to lock, Pull or turn to reset

General data

Peripheral of actuator	AL
Actuator	PA
Mechanical life	$\geq 3 \times 10^5$ Cycles
Operating temperature	-25 to +70°C (-13 to +158°F)
Storage temperature	-30 to +80°C (-22 to +176°F)
Protection Degree	IP 65

Order code

Style	Actions	Contact	Part No.	Note
Emergency Stop Switches	Push to lock, Pull or turn to reset	In place of □ insert contact as follows: 01:1NC 02:2NC 03:3NC	PB-22D-□Z	In place of ① insert voltage and ② LED color from tab
Illuminated Emergency Stop Switches			PB-22D-□ZD/②①	

1. Except for the listed products models, Special and Customized Products are available. Please consult the factory for more details

Dimensions (mm)

