

Type PB Key Selector Switches

- $\Phi 22\text{mm}$
- Front bezel (Aluminium):circular
- Holder : Nut
- Self-hold or spring return
- Two and three positions
- IEC/EN 60947-5-1,UL 508,IEC/EN 60073, IEC/EN 60529



Product description

Key selector switches are mechanical switches that can be turned right, center or left to open or to close the electric contacts. Mostly used to switch between two/three circuits. when the key is pulled-out no any other action can be done.

Type

Y= Key Selector Switches

Actions

21=Two positions L R
31=Three positions L C R

Key extraction position※

L = on the left position
C = on the center position
R = on the right position

General data

Peripheral of actuator	AL
Actuator	PA
Mechanical life	$\geq 3 \times 10^5$ times
Operating temperature	-25 to + 70°C (-13 to +158°F)
Storage temperature	-30 to + 80°C (-22 to +176°F)
Protection Degree	IP 65

Order code

Style	Actions	Contact	Part No.	Note
Key Selector Switches	Two Positions	For contact details, See pg.32	PB-22D-□Y▲■	
	Three Positions		PB-22D-□Y▲■	

1. In place of ▲ insert actions table
2. In place of ■ insert Key extraction position table
3. Except for the listed products models, Special and Customized Products are available. Please consult the factory for more details

Dimensions (mm)

